


WideTEK WT36C-600



Scanning Speed

The scanning speed depends on the settings for resolution and color depth. In grayscale scanning, the WideTEK scanners use photometric correct white light. This produces the best possible images.



The following table shows the scan speed depending on the resolution.



Relation between Documents Length and Resolution

The maximum document length depends on three factors, resolution, color depths and document width. The WT36C-600 has 8 GB memory build into the scanner, enough to scan a 36" wide document at 300dpi up to a length of 647" or 16,4m. The following tables show the relation between the scanning length, document width, resolution, and color depth.

24bit Color:



Optical System

Document width	38 inches / 965 mm
Scan width	36 inches / 915 mm
Maximum document thickness	0.05 inch / 1.5 mm
Scan direction	Face up
Scanner resolution	1200 x 1200 dpi
Optical resolution	1200 x 600 dpi
Pixel dimension	42 x 42 µm
Sensor type	Three dual light CIS modules
Grayscale digitization	12 bit (internal resolution)
Color digitization	36 bit (internal resolution)
Scan modes	24 bit color, 8 bit color, 8 bit grayscale, bitonal, enhanced halftone

Accuracy and Stitching

Accuracy in scan direction	± 0.08% across 36 inch scanning width
Accuracy in transport direction	± 0.08% with new transport rollers

Illumination System

Light source	Approx. 1000 LEDs on two sides
Warm-up time	None
Temperature dependency	None
UV / IR emission	None
Lifetime	50,000 hours (typ.)

Electrical Specifications

External Power Supply

Voltage	100 – 240 V AC
Frequency	47 – 63 Hz
Inrush current	120 A max / 264 V AC
Efficiency	85 %
Operating temperature	5 to 40 °C / 40 to 105 °F
Operating humidity	20 ... 80 % RH, non-condensing
ECO standard	CEC level V

Scanner

Voltage	24 V DC
Current	Max. 5 A

Power Consumption

Sleep	≤ 0.5 W
Standby	4.8 W
Ready to scan	35 W
Scanning	55 W

Dimensions and Weight

Scanner outer dimensions	195 x 1100 x 410 mm (H x W x D) 7.7 x 43.3 x 16.1 inches
Scanner outer dimensions (incl. floor stand)	1045 x 1100 x 410 mm (H x W x D) 41.2 x 43.3 x 16.1 inch
Weight of scanner	30 kg / 66 lbs.
Weight of floor stand incl. paper catch and monitor table	35 kg / 77 lbs.

Transport Box:

Transport dimensions on a pallet	450 x 1200 x 800 mm (H x W x D) 17.7 x 47.3 x 31.5 inch
Total shipping weight	85 kg / 187 lbs.

Transport Box Bundle:

Transport dimensions on a pallet	660 x 1200 x 800 mm (H x W x D) 25.6 x 47.3 x 31.5 inch
Total shipping weight	108 kg / 238 lbs.

Ambient Conditions

Operating temperature	5 to 40 °C / 40 to 105 °F
Storage temperature	0° to 60 °C, 32° to 140 °F
Relative humidity	20 to 80% (non-condensing)
Noise level	< 35 dB(A) (Operating) < 25 dB(A) (Standby)

© 2011 – 2014 by Image Access GmbH, Wuppertal, Germany.

Printed in Germany. All rights reserved.

Reproduction in whole or in part in any form or medium without express written permission of Image Access is prohibited.

Scan2Net®, WideTEK® and Bookeye® are registered trademarks of Image Access.

All other trademarks are the property of their respective owners.

Image Access reserves the right to change the described products, the specifications or documents at any time without prior notice.

For the most recent version, always check our web site www.imageaccess.de or www.imageaccess.us or the customer service portal at portal.imageaccess.de